

# SAFETY DATA SHEET (SDS)

**Wood Dust**

*Prepared according to U.S. OSHA, CMA, ANSI, Canadian WHMIS regulations*

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **Wood Dust**  
PRODUCT DESCRIPTION: Particles generated by manual or mechanical cutting or abrasion process performed on wood.  
U.N. NUMBER: None  
U.N. DANGEROUS GOODS CLASS: Non-Regulated Material  
SUPPLIER/MANUFACTURER'S NAME:  
ADDRESS:  
BUSINESS PHONE:  
WEB SITE:  
DATE OF PREPARATION:  
DATE OF LAST REVISION: June 6, 2018

## SECTION 2 - HAZARDS IDENTIFICATION

**WARNING!** Wood Dust may form combustible dust concentrations in air (during processing).

### EMERGENCY OVERVIEW:

**APPEARANCE AND ODOR:** Wood Dust is a light to dark colored granular solid with odor dependent upon wood species and time since dust was generated.

**HEALTH HAZARDS:** The primary health hazard posed by this product is dust inhalation which can cause respiratory system irritation. Contact with skin and eyes can also cause irritation. Prolonged or repeated inhalation of wood dust may cause cancer.

**FLAMMABILITY:** Depending on the moisture content and particulate diameter, wood dust may explode in the presence of an ignition source. An airborne concentration of 40 grams of dust per cubic meter of air is often used as the LEL for wood dusts.

**ENVIRONMENTAL EFFECTS:** The Environmental effects of this product have not been investigated, however this product is not anticipated to cause adverse environmental effects.

### US DOT SYMBOLS

Non-Regulated

### CANADA (WHMIS) SYMBOLS

Not Controlled

### GHS HAZARD SYMBOL(S)



Signal Word: **Warning!**

### COMPONENTS DETERMINING HAZARDS:

Wood Dust

### GHS HAZARD CLASSIFICATION(S):

Carcinogen Category 2  
Eye Irritation Category 2B  
Skin Irritation Category 3  
STOT SE Category 3

### HAZARD STATEMENTS:

Suspected of causing cancer  
Causes eye irritation  
Causes mild skin irritation  
May cause respiratory irritation

### PRECAUTIONARY STATEMENTS:

Avoid exposure  
Use only with adequate ventilation.  
Wash thoroughly after handling.

# SAFETY DATA SHEET (SDS)

Wood Dust

## HEALTH HAZARDS OR RISKS FROM EXPOSURE:

### ACUTE:

**INHALATION:** Exposure to wood dust may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system.

**EYE CONTACT:** Direct eye contact can cause irritation with redness, tearing and blurred vision.

**SKIN CONTACT:** May cause skin irritation.

**INGESTION:** Ingestion of this product is not a likely route of entry.

**CHRONIC:** Wood Dust is listed as a carcinogen by NTP, OSHA, or IARC. IARC – Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing association exposure to wood dust and Adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and other cancers.

**TARGET ORGANS:** ACUTE: Eye, Skin, Respiratory System CHRONIC: Respiratory System

## SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

**HAZARDS DISCLOSURE:** This product does contain known hazardous materials in reportable levels as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200. As defined under SARA 311 and 312, this product contains known hazardous materials.

HAZARDOUS INGREDIENTS:	CAS #	WT %	HAZARD CLASSIFICATION; RISK PHRASES
Wood Dust	Not Listed	100%	HAZARD CLASSIFICATION: Carcinogen Cat 2, [Xi] Irritant RISK PHRASES: R36/37/38

Each of the other components present are less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens)

**NOTE:** ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format.

## SECTION 4 - FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and SDS to health professional with contaminated individual.

**EYE CONTACT:** If wood dust enters the eyes, open eyes while under gentle running water for 15 minutes. Seek medical attention if irritation or blurred vision continues.

**SKIN CONTACT:** Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists.

**INHALATION:** If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention immediately.

**INGESTION:** If wood dust is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with pre-existing skin disorders or respiratory conditions may aggravate condition by exposure to wood dust.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and reduce over-exposure.

## SECTION 5 - FIRE-FIGHTING MEASURES

**FLASH POINT:** Not Applicable

**AUTOIGNITION TEMPERATURE:** Dependent upon duration of exposure to heat source and other

# SAFETY DATA SHEET (SDS)

Wood Dust

variables Typ. 400-500°F (204-260°C)

## FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL): See below under "UNUSUAL FIRE AND EXPLOSION HAZARDS"

Upper (UEL): Not Established

**FIRE EXTINGUISHING MATERIALS:** Dry chemical, carbon dioxide, foam. Do not use forced stream as this could cause fire to spread.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Wood dust is a strong to severe explosion hazard if a dust cloud contacts an ignition source. Depending on the moisture content and particulate diameter, wood dust may explode in the presence of an ignition source. An airborne concentration of 40 grams of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards 654 and 664 for guidance.

Explosion Sensitivity to Mechanical Impact: Not Sensitive.

Explosion Sensitivity to Static Discharge: Not Sensitive

## SPECIAL FIRE-FIGHTING PROCEDURES:

NFPA Rating System



Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**SPILL AND LEAK RESPONSE:** Avoid accumulation of dried wood dust on exposed surfaces. Avoid actions that cause dust to become airborne. Dried wood dust may pose a combustible dust hazard. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment as described in Section 8.

Cleanup using shovel, sweeping or vacuum. Avoid dry sweeping which creates dust. Apply water spray to prevent airborne dust. Scrape up wet material and place in an appropriate container.

## SECTION 7 - HANDLING and STORAGE

**WORK PRACTICES AND HYGIENE PRACTICES:** Minimize dust generation and accumulation on surfaces. Avoid dusty conditions and provide good ventilation. Avoid eye contact. Avoid repeated or prolonged contact with skin. Careful bathing and clean clothes after exposure. Avoid prolonged or repeated breathing of wood dust in the air.

**STORAGE AND HANDLING PRACTICES:** Wood dust may pose a combustible dust hazard. Keep away from ignition sources. Avoid contact with oxidizing agents and drying oils. Avoid open flame.

## SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

### EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Wood Dust	Not Assigned	1.0mg/m <sup>3</sup> Inhalable All Other Species 0.5mg/m <sup>3</sup> Inhalable Western Red Cedar	15 mg/m <sup>3</sup> Total Dust 5.0 mg/m <sup>3</sup> Respirable Fraction

Currently, International exposure limits are not established for all the components of this product. Please check with competent authority in each country for the most recent limits in place.

**VENTILATION AND ENGINEERING CONTROLS:** Provide adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne dust.

*The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada. Please reference applicable regulations and standards for relevant details.*

# SAFETY DATA SHEET (SDS)

**Wood Dust**

The design and operation of dust handling systems should consider the potential of combustible hazard.

**RESPIRATORY PROTECTION:** Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

**EYE PROTECTION:** Wear safety glasses as appropriate were contact is possible. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

**HAND PROTECTION:** Wear gloves as appropriate to reduce skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

**BODY PROTECTION:** Use body protection appropriate to prevent skin contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

<b>PHYSICAL STATE:</b>	Solid
<b>APPEARANCE &amp; ODOR:</b>	Wood dust is a light to dark colored granular solid with odor dependent upon wood species and time since dust was generated.
<b>ODOR THRESHOLD (PPM):</b>	Mild
<b>VAPOR PRESSURE (mmHg):</b>	Not Applicable
<b>VAPOR DENSITY (AIR=1):</b>	Not Applicable
<b>EVAPORATION RATE (nBuAc = 1):</b>	Not Applicable
<b>BOILING POINT (°C):</b>	Not Applicable
<b>FREEZING POINT (°C):</b>	Not Applicable
<b>pH:</b>	4 - 6
<b>SPECIFIC GRAVITY 20°C: (WATER =1)</b>	Variable dependent on wood species and moisture content
<b>SOLUBILITY IN WATER (%)</b>	Insoluble
<b>VOC:</b>	Not Applicable

## SECTION 10 - STABILITY and REACTIVITY

**STABILITY:** Wood dust is stable

**DECOMPOSITION PRODUCTS:** Thermal decomposition of this product produces oxides of carbon and potentially toxic fumes and gases.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** Avoid contact with oxidizing agents and drying oils.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Contact with incompatible materials and ignition sources

## SECTION 11 - TOXICOLOGICAL INFORMATION

### TOXICITY DATA:

Wood dust (softwood or hardwood) OSHA hazard rating = 3.3; moderately toxic with probable oral lethal dose to humans being 0.5 – 5 g/kg (about 1 pound for a 150 pound person).

Source: OSHA Regulated hazardous Substances, Government Institutes, Inc.

**SUSPECTED CANCER AGENT:** One or more of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is considered to be, or suspected to be a cancer-causing agent by these agencies.

Wood Dust is listed as a carcinogen by NTP, OSHA, or IARC. IARC – Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing association exposure to wood dust and Adenocarcinoma of the nasal cavities and Paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and other

# **SAFETY DATA SHEET (SDS)**

**Wood Dust**

cancers.

**IRRITANCY OF PRODUCT:** Contact with this product can be irritating to skin and eyes.

**SENSITIZATION OF PRODUCT:** Ingredients in this product are not considered a sensitizer.

**REPRODUCTIVE TOXICITY INFORMATION:** No information available

## **SECTION 12 - ECOLOGICAL INFORMATION**

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**ENVIRONMENTAL STABILITY:** Wood dust in soil contact will degrade readily.

**EFFECT OF MATERIAL ON PLANTS or ANIMALS:** No evidence is currently available on wood dust effects on plants and animals. Wood dust may contain ingredients that are considered hazardous.

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** No evidence is currently available on wood dust effects on aquatic life. Wood dust may contain ingredients that are considered hazardous to aquatic organisms.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate Federal, State, and local regulations, and those of Canada.

Wood dust is not considered hazardous waste under Federal Hazardous Waste Regulations 40 CFR 261.

## **SECTION 14 - TRANSPORTATION INFORMATION**

### **U.S. DOT; IATA; IMO; ADR:**

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

**PROPER SHIPPING NAME:** Non-Regulated Material

**HAZARD CLASS NUMBER and DESCRIPTION:** None

**UN IDENTIFICATION NUMBER:** None

**PACKING GROUP:** None

**DOT LABEL(S) REQUIRED:** None

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004):** None

**MARINE POLLUTANT:** None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

### **U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:**

Wood dust is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

### **TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:**

Wood dust is not classified as Dangerous Goods, per regulations of Transport Canada.

### **INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):**

Wood dust is not classified as Dangerous Goods, by rules of IATA:

### **INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:**

Wood dust is not classified as Dangerous Goods by the International Maritime Organization.

## **SECTION 15 - REGULATORY INFORMATION**

### **UNITED STATES REGULATIONS**

**SARA REPORTING REQUIREMENTS:** Wood dust is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

**TSCA:** All components in this product are not listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

### **SARA 311/312:**

Acute Health: Yes

Chronic Health: Yes

Fire: No

Reactivity: No

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning

# SAFETY DATA SHEET (SDS)

**Wood Dust**

Quantities for wood dust. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

**U.S. CERCLA REPORTABLE QUANTITY (RO):** None

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):**

Wood dust is a substance listed under the California Proposition 65.

**⚠️ WARNING:** Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to [www.p65warnings.ca.gov/wood](http://www.p65warnings.ca.gov/wood).

**CANADIAN REGULATIONS:**

**CANADIAN DSL/NDL INVENTORY STATUS:** All of the components of this product are on the DSL Inventory

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** No component of this product is on the CEPA First Priorities Substance Lists.

**CANADIAN WHMIS CLASSIFICATION and SYMBOLS:** This is not considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and is therefore subject to the labeling and MSDS requirements of the Workplace Hazardous Materials Information System (WHMIS). Labeling not required.

## **SECTION 16 - OTHER INFORMATION**

Refer to NFPA Standards 654 and 664 for safe handling.

*NFPA 654 Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids*

*NFPA 664 Standard for the Prevention of Fires and Explosions in Wood Processing and Woodworking Facilities*

### **Disclaimer:**

This information is furnished without warranty, expressed or implied,  
except that it is accurate to the best knowledge of

The data on this sheet is related only to the specific material designated herein.

assumes no legal responsibility for use or reliance upon this data.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.